


Part Number	494-00033		Revision
Customer P/N	494-00033		Revision
Capacitance	12.5	uF.	Tolerance 6.0%
Voltage	370	VAC	
Dielectric	Metalized Polypropylene		
Terminal Type	.250" Quad-Spade Quick Connect Terminals		
Operating Temperature	-25 °C.-	70 °C.	
Dissipation Factor	0.002	maximum	@ 60 Hz.

MOTOR Capacitors, Inc.

Motor Capacitors, Inc.
 335 Beinoris Drive
 Wood Dale, Illinois 60191
 773-774-6666 (Phone) | 773-774-6690 (Fax)
www.capacitorindustries.com
info@capacitorindustries.com

	Dimension	Tolerance
Width (W)	2.91	0.06
Thickness (T)	1.91	0.06
Height (H)	2.38	max.
Terminal Height (K)	0.50	max.
Bracket Length (B)	2.12	ref.
Reference Curve (R)	2.50	max.

Dimensions in inches



Stamping	MOTOR-CAP
	494-00033
	12.5 uF 370 V
	RU

Oil-Filled Tern Plate Steel Case
With Spot Welded Bracket and Molded Insulators
Black Enamel Finish

Approval: J. D. Aldana
 Date: July 5, 2016