Part Number	**CBB5-3GJ007E**		Revision	
Customer P/N			Revision	
Capacitance	**7.5**	uF.	Tolerance	**5.0%**
Voltage	**370**	VAC		
Dielectric	**Metallized Polypropylene**			
Terminal Type	**Dual .250" X .03" Quick Connect Terminals**			
Operating Temperature	**-25** °C.-	**70** °C.		
Dissipation Factor	**0.0015**	maximum @ 60 Hz.		

MOTOR Capacitors, Inc.

Motor Capacitors, Inc.
335 Beinoris Drive
Wood Dale, Illinois 60191
773-774-6666 (Phone) | 773-774-6690 (Fax)
www.capacitorindustries.com
info@capacitorindustries.com

	Dimension	Tolerance
Diameter (D) Case/Cover	**1.64/1.76**	**0.06**
Case Height (H)	**2.39**	**0.06**
Terminal Height (K)	**0.56**	**ref.**
Terminal-Terminal (M)	**0.81**	**ref.**
Insulating Cup (dia.)	**0.74**	

Dimensions in inches



Stamping

Logo
CBB5
7.5 uF ± 5% 370 VAC
50/60 Hz NO PCB
MAX TEMP 70 °C

ЯU

Approval : *J.D. Aldana*
Date : **June 20, 2005**