

Part Number	CBB65-660V105-M1	Revision	
Customer P/N	21230751090002	Revision	
Capacitance	1	uF.	Tolerance 3.0%
Voltage	660	VAC	
Dielectric	Metallized Polypropylene		
Terminal Type	Two-Spade Quick Connect Terminals		
Operating Temperature	-40 °C.-	85 °C.	
Dissipation Factor	0.001	maximum	@ 60 Hz.

MOTOR Capacitors, Inc.

Motor Capacitors, Inc.
 335 Beinoris Drive
 Wood Dale, Illinois 60191
 773-774-6666 (Phone) | 773-774-6690 (Fax)
www.capacitorindustries.com
info@capacitorindustries.com

	Dimension	Tolerance
Case / Cover Width (W)	2.06/2.15	0.06
Case / Cover Thickness (T)	1.22/1.31	0.06
Case Height (H)	2.25	0.06
Terminal Height (K)	0.56	ref.
Terminal-Terminal (M)	0.81	ref.
Insulating Cup (dia.)	0.74	

Dimensions in inches



Stamping

Wuxi - Motor Cap
CBB65-660V105-M1
1 uF. 3% 660 VAC
-40 - +85 C. 50/60 Hz.
21230751090002
Protected 10,000 AFC
Non PCB Date Code RoHs

Tolerance Dot Marking Required on Cover
White -3%~0% Yellow 0%~+3%

Approval: J. D. Aldana
 Date **November 4, 2004**