

Part Number	CBB66A-550V176R		Revision
Customer P/N			Revision
Capacitance	17	uF.	Tolerance 3.0%
Voltage	550	VAC	
Dielectric	Metallized Polypropylene		
Terminal Type	.250" Quad-Spade Quick Connect Terminals		
Operating Temperature	-25 °C.-	100 °C.	
Dissipation Factor	0.002	maximum	@ 60 Hz.

MOTOR Capacitors, Inc.

Motor Capacitors, Inc.
 335 Beinoris Drive
 Wood Dale, Illinois 60191
 773-774-6666 (Phone) | 773-774-6690 (Fax)
www.capacitorindustries.com
info@capacitorindustries.com

	Dimension	Tolerance
Case / Cover Width (W)	2.80	0.06
Case / Cover Thickness (T)	1.77	0.06
Case Height (H)	3.35	0.06
Terminal Height (K)	0.56	ref.
Terminal-Terminal (M)	0.83	ref.
Insulating Cup (dia.)	0.74	
<i>Dimensions in inches</i>		



Stamping

AHJK - Motor Cap
CBB66A-550V176R
17 uF +/-3% 550VAC
100 C Max. 50/60Hz.
Protected 10,000 AFC
Internal Resistor
RU Non PCB Date Code RoHs

Lighting Capacitor
Internal Resistor 1 watt, 560k

Approval: J. D. Aldana
 Date **December 16, 2011**